



Sodding Bid Sheet

Scope

- A. Refer to site specific plan provided by Green Country Habitat for Humanity (GCHFH) for general and supplementary site conditions.
- B. Contractor to provide all labor, operations, materials, and equipment necessary to complete this work.

Quality Assurance: Transplanted sod shall be uniform in color, leaf, texture and shoot density and be reasonably free of visible imperfections at acceptance.

Product - Lawn Sod: Bermuda sod or one of the local approved strains as approved by GCHFH representative.

Preparation

- A. Examine finished surfaces, grades, topsoil quality and depth. Do not start sodding work until unsatisfactory conditions are corrected.
- B. Loosen topsoil of lawn areas to be sodded. Remove stones, sticks, roots, rubbish, and extraneous matter.
- C. Grade lawn areas to a smooth, free draining and even surface with loose, uniformly fine texture. Roll and rake to remove ridges and fill depressions as required to drain.

Installation

- Lay sod to form a solid mass with tightly fitted joints. Butt ends and sides of sod strips. Do not overlay edges. Stagger strips to offset joints in adjacent courses.
- Install sod top flush with adjacent curbs, sidewalks, drives, drains, meter cans, and abutted lawns, etc.
- Place sod strips parallel to dominant contour.
- Do not install sod on saturated or frozen soil.
- Water sod lightly immediately after laying.
- Roll with water filled, commercial lawn roller to insure contact with subgrade. Immediately after rolling, the sod shall be watered thoroughly.

Clean-Up - Perform cleaning upon completion of work. Remove from site all excess materials, debris, and equipment. Repair damage caused by sodding operations.

Please provide cost per square foot bid to reflect labor, material, and equipment to complete job.

Please reference which site you are bidding, include references, licenses and certifications. For more, including insurance requirements and accounts payable schedule, visit greencountryhabitat.org/bids.